



*AeroWindTech Inc. is an authorized distributor and converter for Rogers Corporation Bisco Silicones division.
Rogers Corporation is an approved manufacturer of ABS 5006 specification per Airbus CML.*



Purpose

ABS5006 is specified for the aerospace manufacturing/repair industries as a floor decking seal, thermal insulation, bulkhead backing and noise and vibration dampening pad and meets **FAR 25.853** requirement as per manufacturers SRM & CMM manuals.

Composition

Low weight cellular silicone one side adhesive. Colors are white, gray or black.

Storage

ABS5006 should be stored in a dry cool environment. Shelf life is 18 months from date of shipment when stored at or below 70°F-80°F and a relative humidity of 45-55%.

Configurations

<u>ABS5006-2A</u>	Width: 9 mm; Thickness: 2 mm	<u>ABS5006-4A</u>	Width: 9 mm; Thickness: 4 mm
<u>ABS5006-2B</u>	Width: 12 mm; Thickness: 2 mm	<u>ABS5006-4B</u>	Width: 12 mm; Thickness: 4 mm
<u>ABS5006-2C</u>	Width: 19 mm; Thickness: 2 mm	<u>ABS5006-4C</u>	Width: 19 mm; Thickness: 4 mm
<u>ABS5006-2D</u>	Width: 25 mm; Thickness: 2 mm	<u>ABS5006-4D</u>	Width: 25 mm; Thickness: 4 mm
<u>ABS5006-2E</u>	Width: 30 mm; Thickness: 2 mm	<u>ABS5006-4E</u>	Width: 30 mm; Thickness: 4 mm
<u>ABS5006-2F</u>	Width: 38 mm; Thickness: 2 mm	<u>ABS5006-4F</u>	Width: 38 mm; Thickness: 4 mm
<u>ABS5006-2G</u>	Width: 50 mm; Thickness: 2 mm	<u>ABS5006-4G</u>	Width: 50 mm; Thickness: 4 mm
<u>ABS5006-2H</u>	Width: 80 mm; Thickness: 2 mm	<u>ABS5006-4H</u>	Width: 80 mm; Thickness: 4 mm

*Additional widths and thicknesses available per ABS5006 specification i.e-6mm thickness.