



MASK-OFF COMPANY

STENCIL PAPERS

PROTECTIVE PAPERS AND FILMS

SPECIALTY COATINGS

P.O. BOX 1148 * 345 WEST MAPLE AVENUE * MONROVIA, CALIFORNIA 91016 * PHONE (626) 359-3261 FAX (626) 359-7160

PROTEX 9759-2LC

USES: **PROTEX 9759-2LC** is a 2 mil polyester film with a clear acrylic adhesive designed to protect various metal surfaces including; polished, clad, bare and heat treated aluminum, stainless steel and various coated and coated plastic surfaces, e.g. stretched acrylic, Plex II, cast acrylic and polycarbonates. It can also be used on membrane switch panels as well as Lexan. A liner is provided for ease in hand or die-cutting. This product is not intended for fly-away applications.
PROTEX 9759-2LC is capable of withstanding prolonged outdoor exposure.

TYPICAL PROPERTIES:

BACKING:	Polyester
Thickness, mils	2
Tensile strength, PSI/mils	30,000
Elongation , % M.D.	106 min
Elmendorf tear, grams/mil	15

ADHESIVE:

Base	Acrylic latex
Adhesion to steel, oz./in. width (At time of manufacture)	7 - 10 (-0.7/+0.1)
PSTC-1 (Modified)	

LINER: Flat

Shelf life is 1 year if stored in a cool dry place, out of direct sunlight.

STOCK ROLL SIZES:

36" X 100 YRDS
48" X 100 YRDS